

Hot Farm Tractor Rules

Weight Class
9500, 11000, 13000

1. **Wide fronts and fenders required. Diesel fuel only**
2. **3000 RPM Max - RPMs checked by photo cell tack before or after hook. All tractors must have a positive throttle stop at the injection pump.**
3. **Cut tires allowed. Radials allowed. 18.4-38, 20.8-38, or 18.4-42**
4. **20" drawbar with 3" opening.**
5. **Fire extinguisher.**
6. **Wheelie bars must be able to support the weight of the tractor and no more than 10" inches above ground, bars should extend 3" inches or more from the furthest rear radius point of the tire.**
7. **Flywheel cover-blanket or 6"x 3/8" steel.**
8. **Kill switch-Diesel tractors; air shut off.**
9. **Dead man throttle.**
10. **Engine side shields.**

Safety Equipment Recommended

Electric fan
Steel Flywheels
Frame tie bars
Roll bars

Hot Farm Tractors Rules

Weight Class
5500, 6500, 7500

1. Naturally aspirated Gas or Diesel only.
2. 18-20 inch draw bar rule with 3" inch opening.
3. 18.4-38 max tire footprint. Cut tires allowed.
4. Rpm unlimited, 3000 RPM above requires safety equipment.
5. Rear Fender Required
6. Flywheel cover- Blanket or 6"x3/8" steel.
7. Engine side shields.
8. Dead Man Throttle.
9. Kill Switch.
10. Wheelie Bars must be able to support the weight of the tractor and no more than 10" inches above ground, bars should extend 3" inches or more from the furthest rear radius point of the tire.
11. Steel shield around fan.

Safety Equipment Recommended

Electric fan
Steel Flywheels
Frame tie bars
Roll bars