

RULES OF STOCK ANTIQUE TRACTOR PULLERS

1958 - 1975

Classes (may vary)

8000

10000

13000

1. Drivers must be 18 years of age or older. Drivers 14 to 18 must have written consent of parents for each pull.
2. Obvious or excessive consumption of alcoholic beverages will be grounds for disqualification.
3. Foul or abusive language will be grounds for disqualification.
4. Drivers must be seated, with one hand on the steering wheel at all times.
5. Tractors must be operated in a safe manner at all times. on or off the track.
6. **Factory Pumps and Factory turbo allowed.**
7. **All Factory Equipment must intact (PTOs 3point).**
8. Tractors must be of two wheel drive type.
9. All fans or exposed moving parts must be shielded .
10. No essential equipment can be removed. Standard tread tractors require fenders. Fenders are optional on row crop tractors.
11. **3.5 mph pace, No shifting up or down allowed during a pull.**
12. Any fuel mixture will be grounds for disqualification.
13. Tractors must be weighed with driver on. If tractor is entered in more than one class, it must weigh for each class.
14. Tractor weight may be protested. Both protester and protested will be reweighed. Judges have the right to reweigh any tractor without protest.
17. Tractors may pull in more than one class, but only once in each class.
18. Weights and parts must be securely fastened to tractor. If anything falls off tractor, it will be disqualified from that class.
19. Anytime any part of the tractor or skid goes outside boundaries it will be disqualified.
20. Tractors must be naturally aspirated. No fuel injection or gas under pressure unless factory equipped.

21. If the track judge stops a puller for any reason, the puller will take the distance where he or she is stopped. If stopped within the first 20' you will be entitled to one restart. No weight changes allowed.
22. Tractors shall be stopped if the front end raises or higher than the track judge thinks is safe.
23. Tractors are allowed factory rated horsepower or factory overhaul replacement horsepower. Judges have the right to check any tractor.
24. Tires must be unaltered factory tread. No cut tires allowed. Rim diameter cannot be any larger than original equipment.
25. Tractors will pull from the clevis fasten by a minimum of 3/4 inch hitch pin or fixed pulling eye of 3 inches. Each puller responsible for his or her own clevis. **Maximum draw bar height is 18 inches.** No closer than 18 inches to axles.

The track judges will have the final decision on all rules and regulations of the pull.